
From: Scott Denett <[REDACTED]>
Sent: Friday, January 28, 2011 8:28 PM
To: Jeffrey Epstein
Subject: Re: specs

here =s what nick gave me

hope this helps. Let =e know if you need anything =lse

Remove TITAN =ference 1080p	Remove TITAN =ference 1080p 3D	Remove =IGHlite Cine 260 HC
110-016		
Aspect =atio	16x9 16x9 2000	
20000		
Display =type	DarkChip™ DMD	DarkChip™ DMD
36		DarkChip™ =MD
Fill =actor	87.00 87.00	Not =pplicable
HDTV =ormat	1080p, 1080i, 480p, 720p, 480i, 576p, 576i	1080p, =080i, 480p, 720p, 480i, 576p, 576i
=080i, 720p, 576p, 576i, 480p, 480i		1080p,
Horizontal Scan Rate	15kHz to 100kHz	15kHz to =00kHz
		Not applicable
Humidity	20 to 80% non-condensing	20 to 80% =on-condensing
		20% to 85%
Lens =ount	Zoom: Motorized horizontal and vertical lens shift, zoom and =ocus.	Fixed: Manual Focus.
		Zoom:
Motorized horizontal and =vertical lens shift, zoom and focus. Fixed: Manual Focus.		Not =pplicable
Mechanical Mounting	Front/Rear Table, Front/Rear Ceiling, =djustable Front/Rear Feet	Front/Rear Table, Front/Rear Ceiling, =djustable Front/Rear Feet
Ceiling, =djustable Front/Rear Feet	Front/Rear Table, Front/Rear Ceiling, =djustable Front/Rear Feet	
Native =esolution	1920 x 1080 Pixels	1920 x 1080 Pixels
		1920 x 1080 =ixels
Operating =emperature	0 to 40°C	0 to =0°C
		0 to 40 C
Power =onsumption	850 850	110-120/200-240 VAC
Remote =ontrol	Remote wireless IR, Wired through 3.5mm stereo jack	Remote =ireless IR, Wired through 3.5mm
stereo jack	Remote =ireless IR	
Safety =egulation	CE, CCC CE, CCC CE, FCC =lass A, UL	
1500		
Vertical =can Rate	24Hz to 85Hz	24Hz to 85Hz 43-85 =Z
Video Compatibility	HDTV, NTSC, =AL-M, PAL, NTSC 4:43, PAL-N, SECAM, HDCP Compliance	HDTV, NTSC, =AL-M, PAL, NTSC 4:43, PAL-N, SECAM, HDCP Compliance
		HDTV, NTSC, =AL, SECAM, PAL-N, HDCP Compliance
Video Processing	Enhanced =even-point Color Correction, Xenon Color Mode, User-selectable preset =nd	
downloadable parametric de-gamma, Pixel-based motion adaptive =nterpolation, Class-leading de-interlacing using 3:2		
and 2:2 =xtraction, Frame Delay: as low as 1 frame, source, Auto mode selection - plug and play setup		Enhanced
Seven-point Color Correction, =enon Color Mode, User-selectable preset and downloadable parametric =e-gamma,		
Pixel-based motion adaptive interpolation, Class-leading =e-interlacing using 3:2 and 2:2 extraction, Frame Delay: as low		
as 1 =frame, source, Auto mode selection - plug and play setup		Automation Control RS232 9-pin D sub / RJ45 LAN
	RS232 9-pin = sub / RJ45 LAN	RS232 9-pin D sub / RJ45 =AN
Computer =ompatibility	Up to 1920 x 1080	Up to 1920 x =080
		Up to 1920 x 1080
Height in =nches	10.00 10.00	218.60
Length in =nches	26.00 26.00	500.60
Width in =nches	21.50 21.50	499.20
Weight in =ounds	68.00 68.00	WeightKg 31.00 31.00
=		Not =pplicable