

---

**From:** J <jeevacation@gmail.com>  
**Sent:** Monday, December 3, 2018 4:48 PM  
**To:** Richard Kahn; Kyle reavis  
**Subject:** Re: punch list for work in bathrooms cabana's 1,2,3,&4

efis? kitchen cabanas mike c=tage. tile main compund NURSERY. gyn doors?♦=A0 windowS?

On Mo=, Dec 3, 2018 at 11:44 AM Richard Kahn <[REDACTED]> wrote:

Richard Kahn  
HBRK Associates Inc.  
575 Lexington Avenue 4th =loor  
New York, NY 10022  
[REDACTED]

Begin forwarded message:

From: Jay Knoepfel <jay@jpkvi.com>

Subject: punch list for work in bathrooms cabana's 1,2,3,&4

Date: D=cember 3, 2018 at 11:41:39 AM EST

To: Richard Kahn <richardkahn12@gmail.com <mailto:=ichardkahn12@gmail.com>>;=brice gordon <bgordon.lsj@gmail.com <mailto:bgordon.lsj@gmail.com>>; Kyle reavis <kyleusvi@gmail.com <mailto:kyleusvi@gmail.com>>

Cabana #1

1. grout line touch up on perime=er of floor tile
- 2.

Adjust window to be parallel with tile walls and fabricate trim t= finish tile surrounding window and paint

- 3.

#### Glass door install

4. extend jamb of entrance door and trim=out glass door area
5. all grout sealed and tile cleaned
6. finish tile install at door  
install shower trim<=div>
7. decide and in=tall threshold at glass shower door
8. round shelf and bench edge

#### Cabana #2

1. touch up floor=grout in two locations
2. replace one floor tile under window
3. round shelf edge
4. extend door jamb and trim =ut to finish glass door install
5. install glass door
6. raise floor drain
7. trim out window and paint trim
8. <=iv style="margin-top:0px; margin-bottom:0px">tile threshold with selected=material

#### Cabana #3

1. replace wall tile marked with blue tap=
2. round over =ile edges◆=A0
3. tu=e up floor grout where grout line exceeds common dimension
4. <=iv style="margin-top:0px; margin-bottom:0px">paint ceiling and drill hole= for lights
5. =rep door opening and plaster to create finished look
6. install glass door
7. final cleaning of tile=and sealing of grout

#### Cabana =4

1. replace tile edge at shelf configure door o=ening for glass door

2. remove and replace one floor tile marked with blue tape  
=li>  
round over edges <=pan class="m\_-8654375518264686230Apple-converted-space">
3. raise floor dra=n
4. install gl=ss door
5. clea= tile and seal grout joints  
=br>

--

please note

The infor=ation contained in this communication is confidential, may be attorney=lient privileged, may constitute inside information, and is intended on=y for the use of the addressee. It is the property of

JEE

Unautho=ized use, disclosure or copying of this communication or any part there=f is strictly prohibited and may be unlawful. If you have received this=br>communication in error, please

notify us immediately by

return e-mai= or by e-mail to conversation-id 319918 date-last-viewed 0 date-received 1543855709 flags 8590195713 remote-id 878081 <mailto:jeevacation@gmail.com>